

according to Regulation (EC) No 1907/2006

Assembly Cement high strength

Revision date: 17.12.2019 Product code: 16-20 Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Assembly Cement high strength

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name: ITW LLC & Co. KG
Street: Mühlackerstrasse 149
Place: D-75417 Mühlacker
Telephone: ++49(0)7041-96340

e-mail: info@itwcp.de Internet: www.itwcp.de

Responsible Department: Produktsicherheit Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

Swiss Toxicological Information Centre - Téléphone : +41 44 251 51 51 (in

Telefax: ++49(0)7041-963429

Switzerland dial 145)

United Kingdom: National Poisons Information Service - Phone number:

8448920111

Österreich: Vergiftungsinformationszentrale Vienna - Telefon-Nummer: +43 1

406 43 43

Schweiz : Tox Info Suisse - Telefon-Nummer : +41 44 251 51 51 Italia : Centro Antiveleni, Roma - Numero di telefono : +39 06 305 4343 España : Instituto Nacional de Toxicología - Teléfono : +34 91 562 04 20

1.4. Emergency telephone

number:

Deutschland: ++49(0)7041-96340

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

Causes serious eye damage. Causes serious eye irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydroxypropyl methacrylate, mixture of isomers Trimethylolpropane ethoxylate triacrylate

Signal word: Warning

Pictograms:







according to Regulation (EC) No 1907/2006

Assembly Cement high strength

Revision date: 17.12.2019 Product code: 16-20 Page 2 of 7

Hazard statements

H318 Causes serious eye damage. H319 Causes serious eye irritation.

Precautionary statements

P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P302+P352 IF ON SKIN: Wash with plenty of water.
P363 Wash contaminated clothing before reuse.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Adhesives, sealants

Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	GHS Classification	•	•	
27813-02-1	Hydroxypropyl methacrylate, mixtur		5-10%	
	248-666-3			
	Eye Irrit. 2A, Skin Sens. 1; H319 H3			
20882-04-6	mono-2-(Methacryloyloxy)ethyl suc		5-10%	
	244-096-4			
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
80-15-9	alpha,alpha-dimethylbenzyl hydrop		<1%	
	201-254-7	617-002-00-8		
	Org. Perox. E, Acute Tox. 3, Acute Chronic 2; H242 H331 H312 H302	in Corr. 1B, Aquatic		
102-82-9	Tributylamin			<1%
	203-058-7			
	Acute Tox. 2, Acute Tox. 3, Acute Tox.	H315		
28961-43-5	Trimethylolpropane ethoxylate triac	<1%		
			01-2119489900-30	
	Eye Irrit. 2, Skin Sens. 1; H319 H31			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off contaminated clothing.

After inhalation

Provide fresh air. In case of breathing difficulties administer oxygen. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with: Water. Subsequently wash off with: Polyethylene glykol 400.



ITW LLC & Co. KG

according to Regulation (EC) No 1907/2006

Assembly Cement high strength

Revision date: 17.12.2019 Product code: 16-20 Page 3 of 7

Remove contaminated, saturated clothing immediately. Medical treatment necessary. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. Rinse immediately carefully and thoroughly with eye-bath or water

After ingestion

If swallowed, immediately drink: Water. Rinse mouth immediately and drink plenty of water. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. ABC powder.

Unsuitable extinguishing media

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Nitrogen oxides (NOx). Carbon monoxide Carbon dioxide (CO2).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

This article doesn't contain dangerous substances or preparations intended to be released under normal or reasonably foreseeable conditions of use.

Advice on protection against fire and explosion

No special fire protection measures are necessary.


Further information on handling

Keep container tightly closed. Keep/Store only in original container.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.





according to Regulation (EC) No 1907/2006

Assembly Cement high strength

Revision date: 17.12.2019 Product code: 16-20 Page 4 of 7

Hints on joint storage

Information about storage in one common storage facility: no restriction.

Further information on storage conditions

Keep container tightly closed. Keep in a cool, well-ventilated place. storage temperature: 10-20°C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Does not contain substances above concentration limits fixing an occupational exposure limit.

8.2. Exposure controls





Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink. No special precautionary measures are necessary.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.gas filtering equipment (EN 141).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: green
Odour: odourless

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Flash point:

not determined

not determined

>100 °C

Explosive properties

not explosive.

Density (at 25 °C): 1,1 g/cm³
Water solubility: Immiscible
Viscosity / dynamic: 10000-16000 mPa·s
(at 25 °C)

SECTION 10: Stability and reactivity



according to Regulation (EC) No 1907/2006

Assembly Cement high strength

Revision date: 17.12.2019 Product code: 16-20 Page 5 of 7

10.1. Reactivity

No data available

10.2. Chemical stability

Product is stable in the test system throughout the duration of the test.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
80-15-9	alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide							
	oral	LD50 mg/kg	382	Rat	IUCLID			
	dermal	LD50 mg/kg	500	Rat	RTECS			
	inhalation (4 h) vapour	LC50	1,4 mg/l	Rat	IUCLID			
	inhalation aerosol	ATE	0,5 mg/l					
102-82-9	Tributylamin							
	oral	ATE mg/kg	500					
	dermal	ATE mg/kg	300					
	inhalation vapour	ATE	0,5 mg/l					
	inhalation aerosol	ATE	0,05 mg/l					

Irritation and corrosivity

Irritating to eyes. Risk of serious damage to eyes.

Sensitising effects

May cause sensitization by skin contact.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

STOT-repeated exposure


No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

The preparation is not dangerous in the sense of Directive 1999/45/EC.





according to Regulation (EC) No 1907/2006

Assembly Cement high strength

Revision date: 17.12.2019 Product code: 16-20 Page 6 of 7

Practical experience

Observations relevant to classification

No data available

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Waste disposal number of contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); plastic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

Other applicable information (land transport)

Not restricted

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

Not restricted

Marine transport (IMDG)

Other applicable information (marine transport)

Not restricted



ITW LLC & Co. KG

according to Regulation (EC) No 1907/2006

Assembly Cement high strength

Revision date: 17.12.2019 Product code: 16-20 Page 7 of 7

Air transport (ICAO-TI/IATA-DGR)

Other applicable information (air transport)

Not restricted

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 9,98 % (109,78 g/l)

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

SECTION 16: Other information

Relevant H and EUH statements (nu	umber and full text)
-----------------------------------	---------------------	---

H242	Heating may cause a fire.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)