# Technical Datasheet



Article No. 16-41

Article Bearing Mount medium

strength

Available sizes

50ml, 250ml, other sizes upon request



#### **Product description / Please note**

VARYBOND® Grade 16-41 universal, medium strength adhesive for the retaining of bearings in bushes and wheels on axles. Replaces mechanical items like wedges, springs or pins.

#### **Application**

The parts should be dry, clean and free of any kind of grease so that the best result can be acheived. Apply directly from the bottle.

# **Pysical Properties**

## **Liquid Product**

Chemical Base Diester of Methacrylic Acid

Colour yellow / flourescent

Viscosity mPas spindle rpm 1/20 500 - 650
Density 1,07 g/m³
Max. thread diameter M12
Max. dap filling 0.15mm

Max. gap filling 0,15mm Flash point > +90°C

Shelf life 12 months at max. 25°C

**Cured Product** 

Initial strenght after 5 - 10 minutes
Functional strenght after 30 - 40 minutes
Final strenght after 3 - 6 hours

Loose break torque N/A
Prevealing torque N/A

Shear strength (DIN 54 452) 8 - 12 N/mm<sup>2</sup>

Thermal range -55°C up to +150 °C

### Storage / Shelf life

Package should not be mixed with other materials. Shelf life is up to 12 months if stored correctly between 5 and 25°C. Package after emptying to be disposed via metal scrap.