



Technical Data Sheet

CRAMOLIN® PROLUB Art. No. 160

Product description

PROLUB is a mixture of high-quality active agents and inhibitors which prevent electrical failures caused by moisture and corrosion. It lubricates all moving parts of precision instruments and electrical equipment and protects them even under high humidity and salty air. It also loosens dirt, rust, scale and seized parts, displaces water and moisture and restores the electrical properties and resistance values. Due to its low surface tension PROLUB penetrates into surface pores and seals out moisture, reducing the maintenance and extending the operational life of the equipment. It does not attack any material in common use and contains no chlorinated solvents.

Application

PROLUB is used for switches, contacts, relays and contact banks, appliances, installations, electric motors, switchgears, switchboards and signaling systems. PROLUB can be used on metals, varnishes, paints, and most rubber and plastics.

Please note

Apply liberally. For accurate work use attached extension tube. PROLUB can be used on dry or wet surfaces. Use it on new, in service or stored equipment. Through high capillary attraction, product also acts at places of difficult access. To guarantee full lubricating and corrosion protection repeat the procedure from time to time.
MSDS.



Technical Data

Color:	yellowish
Specific gravity (20° C):	0,82[g/cm ³]
Odor:	characteristic, mild
Boiling range of the solvents:	180 - 210[° C]
Temperature range:	- 40 to +150 [° C]
Viscosity (20° C):	3,0 mm ² /s
Viscosity oil (40° C):	32 mm ² /s
Dielectric strength:	31,5 kV
Lubrication property:	up to 790kg (Falex)
Film thickness:	1-2µm

Storage / Shelf Life

Shelf life is 2 years if stored correctly.
Package after emptying to be disposed via metal scrap.