

according to Regulation (EC) No 1907/2006

Anti-Spatter Spray

Print date: 30.01.2017 Product code: VB_69 Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Anti-Spatter Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name: ITW LLC & Co. KG
Street: Mühlackerstrasse 149
Place: D-75417 Mühlacker

Telephone: ++49(0)7041-96340 Telefax: ++49(0)7041-963429

e-mail: info@itwcp.de
Internet: www.itwcp.de
Responsible Department: Produktsicherheit

1.4. Emergency telephone ++49(0)7041-96340

number: Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1 Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P102 Keep out of reach of children.

Special labelling of certain mixtures

Ohne ausreichende Lüftung Bildung explosionsfähiger Gemische möglich. Buildup of explosive mixtures possible without sufficient ventilation.

SECTION 3: Composition/information on ingredients



according to Regulation (EC) No 1907/2006

Anti-Spatter Spray

Print date: 30.01.2017 Product code: VB_69 Page 2 of 7

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Re			
75-28-5	isobutane			25-50 %
	200-857-2	601-004-00-0		
	Flam. Gas 1; H220			
8042-47-5	White Spirit			25-50 %
	232-455-8		01-2119487078-27	
	Asp. Tox. 1; H304			
74-98-6	propane			10-25 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
106-97-8	butane			2,5-10 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After inaestion

If swallowed, immediately drink: Water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

Unsuitable extinguishing media

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.



according to Regulation (EC) No 1907/2006

Anti-Spatter Spray

Print date: 30.01.2017 Product code: VB_69 Page 3 of 7

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking.

Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.



according to Regulation (EC) No 1907/2006

Anti-Spatter Spray

Print date: 30.01.2017 Product code: VB_69 Page 4 of 7

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic

Test method

Changes in the physical state

Lower explosion limits: Upper explosion limits:

Ignition temperature: >200 °C

Density: 0,615 g/cm³

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
106-97-8	butane					
	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS	



according to Regulation (EC) No 1907/2006

Anti-Spatter Spray

Print date: 30.01.2017 Product code: VB_69 Page 5 of 7

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
74-98-6	propane	2,36
106-97-8	butane	2,89

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2
Hazard label: 2



Classification code: 5F

Special Provisions: 190 327 625

Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D



according to Regulation (EC) No 1907/2006

Anti-Spatter Spray

Print date: 30.01.2017 Product code: VB_69 Page 6 of 7

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2 14.4. Packing group:

Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277 EmS: F-D, S-U

Other applicable information (marine transport)

EC

Air transport (ICAO)

14.1. UN number: UN1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1 Hazard label: 2.1



Special Provisions: A145 A167 Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger:

IATA-max. quantity - Passenger:

IATA-packing instructions - Cargo:


IATA-max. quantity - Cargo:

150 kg

Other applicable information (air transport)

E0 : Y203

14.5. Environmental hazards





according to Regulation (EC) No 1907/2006

Anti-Spatter Spray

Print date: 30.01.2017 Product code: VB_69 Page 7 of 7

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 9,99 % (61,439 g/l)

National regulatory information

Water contaminating class (D): 2 - water contaminating

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)