

Technical Data Sheet

VARYBOND PENETRATING OIL

Art.-No. VB 71

Colour:	grey liquid
Specific gravity (20° C): [g/cm ³]	0,70
Odour:	characteristic
Boiling range of the solvents: [° C]	180 - 210
Viscosity at 40° C, DIN 51562-1: [cSt]	5
Surface tension: [mN/m]	26

Varybond Penetrating Oil is an extremely efficient penetrating oil to free and lubricate seized and rusted mechanism, screws, nuts and bolts.

Application

Due to its extremely low surface tension it penetrates into hard-to-reach parts and areas and creeps into the smallest openings and dissolves dried grease. It leaves a lubricating film that reduces wear. Therefore it reduces the breakage rate of frozen parts and lowers the maintenance costs. It contains no aggressive solvents and is harmless to metals, rubbers and the most plastics.

Directions

Spray on parts to be treated. Apply liberally and allow a few minutes for complete penetration. Re-apply where required. Rust-locked mechanisms may need to be left overnight before movement will occur. Through high capillary attraction the product also acts at places of difficult access. To guarantee full lubricating and corrosion protection repeat the procedure from time to time.

ITW LLC & Co. KG

Mühlacker Strasse. 149, D-75417 Mühlacker
Telefon +49 7041 96 34 0, Telefax +49 7041 96 34 29
e-mail info@itwcp.de, website www.itwcp.de

Note: Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, ITW makes no representation as to the completeness or accuracy thereof. Information is supplied upon the conditions that the persons receiving the same will make their own as to its safety and suitability for their purpose prior to use. In no event will ITW be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information.

For further information please contact: **ITW LLC & Co. KG**
Spraytec Germany
Mühlacker Str. 149
75417 Mühlacker
Tel. 0049 (0)7041/96340
Fax. 0049 (0)7041/963429