

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Zinc Spray bright

Revision date: 17.03.2021

Product code: VB_83

Page 2 of 9

Signal word: Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P271	Use only outdoors or in a well-ventilated area.
P251	Do not pierce or burn, even after use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P102	Keep out of reach of children.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Zinc Spray bright

Revision date: 17.03.2021

Product code: VB_83

Page 3 of 9

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
106-97-8	butane			30-40%
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			
74-98-6	propane			10-30%
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
1330-20-7	xylene			5-15 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
67-64-1	acetone; propan-2-one; propanone			10-15%
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
	Hydrocarbons, C6, isoalkanes, <5% n-hexane			5-10 %
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
7440-66-6	zinc powder - zinc dust (stabilised)			2,5-5%
	231-175-3	030-001-01-9		
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
64742-95-6	Solvent naphta light			<1%
	265-199-0		01-2119463881-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H304 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

If swallowed, immediately drink: Water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Zinc Spray bright

Revision date: 17.03.2021

Product code: VB_83

Page 4 of 9

Suitable extinguishing mediaCarbon dioxide (CO₂). Foam. Extinguishing powder.**Unsuitable extinguishing media**

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Zinc Spray bright

Revision date: 17.03.2021

Product code: VB_83

Page 5 of 9

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

EN ISO 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	silver grey
Odour:	Solvent/Thinner.

Changes in the physical state

Initial boiling point and boiling range:	-0,5 °C
Flash point:	< 0 °C
Lower explosion limits:	2,5 vol. %
Upper explosion limits:	14,3 vol. %
Ignition temperature:	365 °C
Vapour pressure: (at 20 °C)	246 hPa
Vapour pressure: (at 50 °C)	814 hPa
Density:	0,882 g/cm ³
Solvent content:	9,99 %

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available

10.2. Chemical stability

No data available

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Zinc Spray bright

Revision date: 17.03.2021

Product code: VB_83

Page 6 of 9

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
106-97-8	butane					
	inhalation (4 h) gas	LC50 ppm	273000	Rat	GESTIS	
1330-20-7	xylene					
	dermal	ATE mg/kg	1100			
	inhalation gas	ATE ppm	4500			
67-64-1	acetone; propan-2-one; propanone					
	oral	LD50 mg/kg	5800	Rat	RTECS	
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50	76 mg/l	Rat		
	Hydrocarbons, C6, isoalkanes, <5% n-hexane					
	oral	LD50 mg/kg	>36750	Rat	OECD	Prüfrichtlinie 401
	dermal	LD50 mg/kg	3350	Rabbit	OECD	Prüfrichtlinie 402
	inhalation vapour	LC50 mg/l	259354	Rat	OECD	Prüfrichtlinie 403
64742-95-6	Solvent naphta light					
	oral	LD50 mg/kg	3592	Rat		
	dermal	LD50 mg/kg	3160	Rabbit		
	inhalation (4 h) vapour	LC50 mg/l	6,193	Rat		

SECTION 12: Ecological information**12.1. Toxicity**



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Zinc Spray bright

Revision date: 17.03.2021

Product code: VB_83

Page 7 of 9

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
	Hydrocarbons, C6, isoalkanes, <5% n-hexane					
	Acute fish toxicity	LC50	>1 mg/l	96 h	Fish	
	Acute algae toxicity	ErC50	30 mg/l	72 h	Alge	
	Acute crustacea toxicity	EC50 mg/l	3,87	48 h	Daphnia pulex (water flea)	
64742-95-6	Solvent naphta light					
	Acute fish toxicity	LC50 mg/l	9,22	96 h	Fisch	
	Acute algae toxicity	ErC50	2,9 mg/l	72 h	Alge	
	Acute crustacea toxicity	EC50 mg/l	6,14	48 h	Daphnia magna (Big water flea)	

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36
67-64-1	acetone; propan-2-one; propanone	-0,24

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

- 14.1. UN number:** UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Zinc Spray bright

Revision date: 17.03.2021

Product code: VB_83

Page 8 of 9



Classification code:	5F
Special Provisions:	190 327 625
Limited quantity:	1 L
Transport category:	2
Tunnel restriction code:	D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number:	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
Hazard label:	2.1



Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number:	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2, see SP63

Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	See SP277
EmS:	F-D, S-U

Other applicable information (marine transport)

E0

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
Hazard label:	2.1



Special Provisions:	A145 A167
Limited quantity Passenger:	30 kg G

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Zinc Spray bright

Revision date: 17.03.2021

Product code: VB_83

Page 9 of 9

IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

Other applicable information (air transport)E0
: Y203**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: butane; Hydrocarbons, C6, isoalkanes, <5% n-hexane; Solvent naphta light

2004/42/EC (VOC): 34,98 %

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)