

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Alu-Spray

Product group: Zwischenprodukt

1.2. Relevant identified uses of the substance or mixture and uses advised against**Uses advised against**

Reserved for industrial and professional use.

Acetone is listed as a reportable explosives precursor in Annex II of EU regulation 2019/1148

Aceton ist in Anhang II der EU-Verordnung 2019/1148 als meldepflichtiger

Explosivstoffvorläufer aufgeführt

1.3. Details of the supplier of the safety data sheet

Company name: ITW LLC & Co. KG
Street: Mühlackerstrasse 149
Place: D-75417 Mühlacker
Telephone: ++49(0)7041-96340 Telefax: ++49(0)7041-963429
e-mail: info@itwcp.de
Internet: www.itwcp.de
Responsible Department: Produktsicherheit Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00
Swiss Toxicological Information Centre - Téléphone : +41 44 251 51 51 (in Switzerland dial 145)
United Kingdom : National Poisons Information Service - Phone number : 8448920111
Österreich : Vergiftungsinformationszentrale Vienna - Telefon-Nummer : +43 1 406 43 43
Schweiz : Tox Info Suisse - Telefon-Nummer : +41 44 251 51 51
España : Instituto Nacional de Toxicología - Teléfono : +34 91 562 04 20
România (Romania): Spitalul de Urgenta Floreasca 021 230 8000
Deutschland: ++49(0)7041-96340

1.4. Emergency telephone number:**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Acetone, Hydrocarbons, C6, Isoalkane, Butanol

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 2 of 10

Signal word: Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P211	Do not spray on an open flame or other ignition source.
P210	Keep away from heat. No Smoking.
P271	Use only outdoors or in a well-ventilated area.
P251	Do not pierce or burn, even after use.
P102	Keep out of reach of children.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 3 of 10

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
106-97-8	butane			30-60 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			
74-98-6	propane			<25 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
67-64-1	acetone; propan-2-one; propanone			10-30%
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
	Hydrocarbons, C6, isoalkanes, <5% n-hexane			5-15%
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
1330-20-7	xylene			5-10%
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
100-41-4	ethylbenzene			<5%
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
64742-48-9	Hydrocarbons, C9-C11, n-Alkane, iso-Alkane			<10%
	265-150-3		01-2119457273-39	
	Asp. Tox. 1; H304			
7429-90-5	aluminium powder (stabilised)			<10 %
	231-072-3	013-002-00-1		
	Flam. Sol. 1, Water-react. 2; H228 H261			
79-24-3	nitroethane			<1%
	201-188-9	609-035-00-1		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4; H226 H332 H302			
108-03-2	1-nitropropane			<1%
	203-544-9	609-001-00-6		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4; H226 H332 H312 H302			
71-36-3	butan-1-ol; n-butanol			<1%
	200-751-6	603-004-00-6		
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 4 of 10

or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

If swallowed, immediately drink: Water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂). Foam. Extinguishing powder.

Unsuitable extinguishing media

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 5 of 10

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
7429-90-5	Aluminium metal, respirable dust	-	4		TWA (8 h)	WEL
71-36-3	Butan-1-ol	50	154		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
79-24-3	Nitroethane	20	62		TWA (8 h)	EU
		100	312		STEL (15 min)	EU
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

EN ISO 374 Tested protective gloves are to be worn: NBR (Nitrile rubber) For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. NBR (Nitrile rubber)

Skin protection

Protective clothing:

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 6 of 10

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	silver grey
Odour:	characteristic

Changes in the physical state

Flash point:	<0 °C
Vapour pressure: (at 20 °C)	2100 hPa
Vapour pressure: (at 50 °C)	4900 hPa
Density:	0,86 g/cm ³

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information**11.1. Information on toxicological effects**



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 7 of 10

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
106-97-8	butane					
	inhalation (4 h) gas	LC50 ppm	273000	Rat	GESTIS	
67-64-1	acetone; propan-2-one; propanone					
	oral	LD50 mg/kg	5800	Rat	RTECS	
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50	76 mg/l	Rat		
1330-20-7	xylene					
	dermal	ATE mg/kg	1100			
100-41-4	ethylbenzene					
	oral	LD50 mg/kg	3500	Rat	GESTIS	
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat		
79-24-3	nitroethane					
	oral	ATE mg/kg	500			
108-03-2	1-nitropropane					
	oral	ATE mg/kg	500			
	dermal	ATE mg/kg	1100			
71-36-3	butan-1-ol; n-butanol					
	oral	ATE mg/kg	500			

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone						
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna		
100-41-4	ethylbenzene						
	Acute algae toxicity	ErC50	3,6 mg/l	96 h		GESTIS	

12.3. Bioaccumulative potential

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 8 of 10

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36
67-64-1	acetone; propan-2-one; propanone	-0,24
100-41-4	ethylbenzene	3,15

SECTION 13: Disposal considerations**13.1. Waste treatment methods****List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 625
Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN1950

Other applicable information (inland waterways transport)

AEROSOLS

Marine transport (IMDG)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2, see SP63

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 9 of 10

Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: See SP277
 EmS: F-D, S-U

Other applicable information (marine transport)

E0

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
 Hazard label: 2.1



Special Provisions: A145 A167 A803
 Limited quantity Passenger: 30 kg G
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

E0

: Forbidden
 : Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
 Entry 28: butane; Hydrocarbons, C9-C11, n-Alkane, iso-Alkane

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
 H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H228 Flammable solid.
 H229 Pressurised container: May burst if heated.
 H261 In contact with water releases flammable gases.
 H302 Harmful if swallowed.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Alu-Spray

Revision date: 17.03.2021

Product code: VB_84

Page 10 of 10

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)