

according to Regulation (EC) No 1907/2006

Grease Spray

Revision date: 18.11.2019

Product code: VB_89

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Grease Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	ITW LLC & Co. KG	
Street:	Mühlackerstrasse 149	
Place:	D-75417 Mühlacker	
Telephone:	++49(0)7041-96340	Telefax:++49(0)7041-963429
e-mail:	info@itwcp.de	
Internet:	www.itwcp.de	
Responsible Department:	Produktsicherheit Mo Do. 8.00 - 1	6.30 Fr. 8.00 - 14.00
	Swiss Toxicological Information Cen	itre - Téléphone : +41 44 251 51 51 (in
	Switzerland dial 145)	
	United Kingdom : National Poisons 8448920111	Information Service - Phone number :
	Österreich : Vergiftungsinformations 406 43 43	zentrale Vienna - Telefon-Nummer : +43 1
	Schweiz : Tox Info Suisse - Telefon-	Nummer: +41 44 251 51 51
	Italia : Centro Antiveleni, Roma - Nu	ımero di telefono : +39 06 305 4343
	España : Instituto Nacional de Toxic	ología - Teléfono : +34 91 562 04 20
1.4. Emergency telephone	Deutschland: ++49(0)7041-96340	

<u>number:</u>

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1 Skin corrosion/irritation: Skin Irrit. 2 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation	(EC) No.	1272/2008
regulation	\ =-,	,	

···· J····· (= -) ····	
Signal word:	Danger

Pictograms:



Hazard statements

H222	
H229	

Extremely flammable aerosol. Pressurised container: May burst if heated.



according to Regulation (EC) No 1907/2006

	Grease Spray	
Revision date: 18.11.2019	Product code: VB_89	Page 2 of 7
H315	Causes skin irritation.	
H411	Toxic to aquatic life with long lasting effects.	
Precautionary statemen	its	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P273	Avoid release to the environment.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P251	Do not pierce or burn, even after use.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	GHS Classification	•	•		
106-97-8	butane			25-50 %	
	203-448-7	601-004-00-0			
	Flam. Gas 1; H220		•		
74-98-6	propane			15-30 %	
	200-827-9	601-003-00-5			
	Flam. Gas 1; H220				
8042-47-5	White Spirit			10-209	
	232-455-8		01-2119487078-27		
	Asp. Tox. 1; H304				
927-356-8	Hyrdrocarbons, C9-C11, n-alkane,	isoalkane, cyclic, <2% aromatic		1-10%	
			01-2119463258-33		
	Flam. Liq. 3, STOT SE 3, Asp. Tox.	1; H226 H336 H304			
	Hydrocarbons, C6, isoalkanes, <5%	% n-hexane		1-5%	
	931-254-9		01-2119484651-34		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE H411	3, Asp. Tox. 1, Aquatic Chronic 2;	H225 H315 H336 H304		

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

If swallowed, immediately drink: Water.

<u>4.2. Most important symptoms and effects, both acute and delayed</u> No data available



according to Regulation (EC) No 1907/2006

Grease Spray

Revision date: 18.11.2019

Product code: VB_89

Page 3 of 7

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

Unsuitable extinguishing media

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

Grease Spray

Revision date: 18.11.2019

Product code: VB_89

Page 4 of 7

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

8.2. Exposure controls





Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	Aerosol whitish characteristic		
Changes in the physical stat	te		
Flash point:		<0 °C	
Density:		0,82 g/cm³	

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.



according to Regulation (EC) No 1907/2006

Grease Spray

Revision date: 18.11.2019

Product code: VB 89

Page 5 of 7

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products No data available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
106-97-8	butane					
	()5	LC50 273000 ppm	Rat	GESTIS		

SECTION 12: Ecological information

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)	
<u>14.1. UN number:</u>	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
Hazard label:	2.1
Classification code:	5F



according to Regulation (EC) No 1907/2006

	Grease	Spray	
Revision date: 18.11.2019	Product co		Page 6 of 7
Special Provisions:	190 327 625		
Limited quantity:	1 L		
Transport category: Tunnel restriction code:	2 D		
	_		
Other applicable information (land trans	sport)		
Inland waterways transport (ADN)			
<u>14.1. UN number:</u>	UN1950		
Other applicable information (inland wa AEROSOLS	terways transport)		
Marine transport (IMDG)			
<u>14.1. UN number:</u>	UN1950		
14.2. UN proper shipping name:	AEROSOLS		
14.3. Transport hazard class(es):	2		
14.4. Packing group:	-		
Hazard label:	2, see SP63		
Special Provisions: Limited quantity: EmS: Other applicable information (marine tra E0	63, 190, 277, 327, 34 See SP277 F-D, S-U ansport)	44, 959	
Air transport (ICAO-TI/IATA-DGR)			
<u>14.1. UN number:</u>	UN 1950		
14.2. UN proper shipping name:	AEROSOLS, flamma	able	
14.3. Transport hazard class(es):	2.1		
Hazard label:	2.1		
Special Provisions:	A145 A167 A802		
Limited quantity Passenger:	30 kg G		
IATA-packing instructions - Passenger:		203	
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:		75 kg 203	
IATA-max. quantity - Cargo:		150 kg	
Other applicable information (air transp : Y203 E0 0000000005: Forbidden 14.5. Environmental hazards	ort)		
ENVIRONMENTALLY HAZARDOUS:	no		
SECTION 15: Regulatory information			

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



according to Regulation (EC) No 1907/2006

Grease Spray

Revision date: 18.11.2019

Product code: VB_89

Page 7 of 7

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 28: butane

National regulatory information

Water contaminating class (D):

2 - clearly water contaminating

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)